

UNCLASSIFIED

AD NUMBER	
AD517835	
CLASSIFICATION CHANGES	
TO:	unclassified
FROM:	confidential
LIMITATION CHANGES	
TO:	Approved for public release, distribution unlimited
FROM:	Distribution authorized to U.S. Gov't. agencies only; Test and Evaluation; OCT 1971. Other requests shall be referred to Commanding Officer, Air Force Rocket Propulsion Laboratory, Attn: [RPOR/STINFO], Edwards AFB, CA 93523.
AUTHORITY	
AFRPL ltr, 14 Apr 1978; AFRPL ltr, 14 Apr 1978	

THIS PAGE IS UNCLASSIFIED

CONFIDENTIAL

AFRPL-TR-71-126 ✓

(2)

✓
AD 517835
DDC FILE COPY

QUARTERLY PROGRESS REPORT
THERMALLY STABLE
BURNING RATE ACCELERATORS (U)

Contract F04611-70-C-0066 ✓

October 1971

Distribution limited to U.S. Govt. agencies only.
Test and Evaluation; 1 AUG 1971 Other requests
for this document must be referred to

Prepared for
Air Force Systems Command
Air Force ^{ROCKET} Propulsion Laboratory
Edwards Air Force Base, California 93523

Attn: RPOR-ST/INFO

Prepared by

Thiokol / HUNTSVILLE DIVISION

Huntsville, Alabama

A DIVISION OF THIOKOL CHEMICAL CORPORATION



CONFIDENTIAL

Distribution limited to U.S. Gov't. agencies only;

Test and Evaluation; 3 Nov 71. Other requests

for this document must be referred to AFRPL (REPORT-STINFO)

Edwards AFB, Calif. 93523.

Attenly

PROCESS ON FOR	
SYSTEM	WHITE SECTION <input type="checkbox"/>
DOC	OF SECTION <input checked="" type="checkbox"/>
DATE	
CLASSIFICATION	
STATE OF	
B	

CONFIDENTIAL

(This Page is Unclassified)

(18) (19)
AFRPL TR-71-126

(14) 32-71

Control No. C-71-32A

Copy No. 10

QUARTERLY PROGRESS REPORT

1 June through 31 August 1971.

⑥ THERMALLY STABLE BURNING RATE ACCELERATORS (U).

Contract F04611-70-C-0066

(11) October 1971

Prepared for
Air Force Systems Command
Air Force Rocket Propulsion Laboratory
Edwards Air Force Base, California 93523

Prepared by

Thiokol / HUNTSVILLE DIVISION
Huntsville, Alabama

A DIVISION OF THIOKOL CHEMICAL CORPORATION

Distribution limited to U.S. Gov't. agencies only;
Test and Evaluation; 3 NOV 1971. Other requests
for this document must be referred to

AFRPL (RPR/STINFO), Edwards
Air Force Base, California 93523.

DEFENSE INFORMATION

This document contains information affecting the national defense of the United States within the meaning of the Espionage Laws, Title 18 U.S.C., sections 793 and 794. The transmission or the revelation of its contents in any manner to an unauthorized person is prohibited by law.

DOWNGRADING INFORMATION

Downgraded at 3 year intervals. Declassified after 12 years. DOD Dir 5200.10

DOWNGRADED AT 3 YEAR INTERVALS;
DECLASSIFIED AFTER 12 YEARS
DOD DIR 5200.10

CONFIDENTIAL

UNCLASSIFIED

CONTENTS

	<u>Page</u>
Foreword	iii
Abstract	iv
Introduction	1
Program Objectives	2
Discussion	5
Task I - Thermally Stable AP	5
Task II - Thermally Stable Catalysts	8
Distribution	

UNCLASSIFIED

FOREWORD

This report is prepared in accordance with the requirements of Contract F04611-70-C-0066.


Program Structure Number	623148
Program Number	3148
Program Element Number	6.23.02F
Program Monitors	Capt C. L. Ennis and Capt D. J. Yardley USAF/RPMPC
Prime Contractor	Thiokol Chemical Corporation Huntsville Division Huntsville, Alabama

This report, the fifth quarterly progress report to be issued under this program, covers effort performed for the period 1 June 1971 through 31 August 1971. This report has been assigned the Thiokol internal number 32-71 (Control No. C-71-32A).

The principal investigators on the program are Dr. W. D. Stephens, Dr. D. A. Flanigan, and Mr. J. O. Hightower. Dr. M. Miller is serving as Program Manager. In addition to those contributions by the principal investigators, major contributions to the program were made by Dr. T. C. Willis, Messrs. J. W. Blank, C. M. Christian, Mrs. Patricia B. Walters, and Dr. R. E. Rogers. The over-all Project Director is Mr. G. F. Mangum.

STATEMENT OF APPROVAL

Publication of this report does not constitute Air Force approval of the report's findings or conclusions. It is published only for the exchange of ideas.



G. F. Mangum
Project Director

UNCLASSIFIED

ABSTRACT

(U) Experiments have shown that the thermal stability of propellants is a direct function of the UFAP and catalyst concentration. A new thermally stable catalyst (dimethylpolyferrocenylmethylene) has been synthesized and is undergoing preliminary evaluation. Indications are that fast burning propellants (2.5 in/sec at 1000 psi) which exhibit good thermal stability (less than 1% weight loss in 10 hours at 350° F), can be made using up to 30% UFAP and up to 3% catalyst.

UNCLASSIFIED

CONFIDENTIAL

INTRODUCTION

(C) The purpose of this program is to research the methods and materials that will produce thermally stable AP and burning rate catalyst. They will be used with other thermally stable propellant ingredients to produce a solid propellant that is capable of withstanding a temperature environment of -75° to 350°F .

(C) With the present capability of aircraft to fly at supersonic speeds, a new requirement now exists for missiles which can be carried externally. The major development problem arises from the effects of aerodynamic heating, causing missile skin temperatures of several hundred degrees Fahrenheit. In addition, the external carry means that a missile in the air-stream is exposed to temperatures of about -65°F (the temperature in the isothermal layer). Missiles and missile components therefore are subject to temperatures from -65°F to well over 300°F .

(C) Propellants that will survive this treatment, and also possess the desirable ballistic properties, are not available. Two general approaches to assure the rocket motor's operation at all times are to insulate the motor or develop a propellant to withstand the environment. Internal or external insulations increase the motor cross sectional area and weight. Also, internal insulation decreases propellant volume. Since the missile is normally exposed to these conditions for a relatively short time, the insulation approach is inefficient. The penalties paid for insulation are too great; thermally stable propellant is a better solution.

CONFIDENTIAL

PROGRAM OBJECTIVES AND ORGANIZATION

OBJECTIVES:

(C). Very small particle oxidizer (less than one micron) and burning rate catalysts have been used to achieve high burning rates; however, commercially available ammonium perchlorate is prone to thermal decomposition which, in turn, degrades propellant. Some liquid burning rate catalysts also have undesirable characteristics such as crystallization, migration, or volatilization and are subject to thermal and oxidative decomposition. The objectives of this program are: (1) to develop methods of production of stable ultrafine ammonium perchlorate (UFAP), (2) to demonstrate improved methods of burning rate catalysis, and (3) utilization of these rate augmentation techniques in propellants which must survive temperature cycling up to 350°F.

PROGRAM ORGANIZATION:


(U) This program is divided into three tasks as follows:

Task I, Thermally Stable UFAP, is subdivided into three subtasks. The first defines AP thermal stability and identifies the qualities that AP must have to be stable. In the second, new methods of preparing UFAP are examined and in the third subtask, the method of preparing UFAP is chosen and enough UFAP prepared for the demonstration part of the program.

Task II, Thermally Stable Catalysts, is divided into four subtasks. These include impurity investigations, structure investigations, improved catalysts, and synthesis of material for Task III.

Task III, Demonstration, is that part of the program in which the thermally stable UFAP and an improved catalyst are combined into a propellant for demonstration.

UNCLASSIFIED



PROGRAM OUTLINE

UNCLASSIFIED

CONFIDENTIAL

TECHNICAL ACCOMPLISHMENTS

Task I - Thermally Stable Ammonium Perchlorate

Introduction

(U) With satisfactory thermal stability obtained with both the ultrafine ammonium perchlorate and ferrocene containing catalyst, experiments were designed to determine how much UFAP and catalyst could be incorporated into a high performance propellant without deleterious effect upon thermal stability.

UFAP Concentration Effects

(C) Small mixes (e.g., 10 g each) of propellant containing R45M HTPB/IPDI as the binder, 10% Al, 70% AP, and zero catalyst were prepared. The AP (pre-purified) was a blend of nominal 40 micron large fraction and 0.8 micron small fraction. The UFAP was prepared by spray freeze dry techniques and was incorporated in the various mixes at the 5, 15, 25, 40 and 60% levels. TGA data was obtained for 20 hours at 190°C on each cured sample. The propellant weight loss at the end of 20 hours of exposure served as the criterion for assessing the effect of UFAP concentration on thermal stability.

(U) The results are shown in the following table. The expected result of decreasing thermal stability with increasing UFAP concentration is noted.

UFAP Concentration Effects (375°F)

<u>% UFAP in Propellant</u>	<u>Time to 1% Wt. Loss</u> (hr)	<u>% Wt. Loss at 20 Hrs.</u>
5	11.00	2.09
15	8.42	3.15
25	6.33	3.75
40	6.20	4.37
60	5.10	5.67

Catalyst Concentration Effects

(U) Small mixes of propellant, such as described above, were prepared in which various amounts (0.2, 0.5, 1.0, 2.0, and 3.0%) of the binder were replaced with polyferrocenylmethylene (PFM) burn rate catalyst. The fine AP concentration was selected so that AP size effects, if any, were of secondary importance. Forty micron pre-purified AP was used as the single oxidizer fraction. TGA data were obtained for 6 hours at 160°C on each cured sample. Percent weight loss after 20 hours exposure was likewise noted.

CONFIDENTIAL

(U) The results are shown in the following table. The anomaly in the 20-hour data for 1% PFM was rechecked by running another isothermal TGA at 160°C. The resulting data (parentheses) is more in line with the expected trend.

Catalyst Concentration Effects (160°C)

<u>% PFM</u>	<u>% Wt. Loss at 6 Hrs.</u>	<u>% Wt. Loss at 20 Hrs.</u>
0.2	0.10	0.69
0.5	0.22	1.25
1.0	0.47 (0.59)	1.18 (1.80)
2.0	0.68	2.16
3.0	0.74	2.32

(C) Following a determination of the effect of UFAP concentration on thermal stability and a similar set of experiments designed to elucidate catalyst concentration effect upon thermal stability, a series of mixes was manufactured in which UFAP/catalyst interactions were examined. Small mixes of propellant (70AP/10A1/HTPB/IPDI) were manufactured. The UFAP utilized in the phase of testing was prepared by the spray freeze dried technique and exhibited an average particle diameter 0.78 microns. The remaining AP was prepurified by flash precipitation from isopropyl alcohol. The catalyst utilized in this study was polyferrocenyl methylene (PFM). The polymer, curing agent and aluminum were predried before mix manufacture.

(U) The mix matrix contained three separate UFAP concentrations and three catalyst concentrations at each UFAP concentration. The UFAP concentrations examined were 10, 30 and 60% and at each of these concentrations the catalyst content was varied from 0.2 to 3.0% (Table I).

(U) Isothermal TGA's were performed at 160°C and the weight loss at the end of 6 hours exposure served as a criterion for assessing any interaction effects on thermal stability. The test matrix and the results are shown on Table I. It is apparent from these experiments that increases in UFAP concentration do not appear to significantly degrade thermal stability. The expected effect of a decrease in thermal stability with increasing catalyst concentration is apparent. It appears from these data that good (less than 1% weight loss) thermal stability can be achieved at 350°F for at least ten hours in propellants containing 30% UFAP and 1-2% PFM. This judgement is based upon the fact that these samples examined by TGA were 1/4-inch cubes and exposed very large surface per unit weight. The percent weight loss will decrease markedly with decreasing surface area to weight ratios.

UNCLASSIFIED

TABLE I
UFAP/CATALYST INTERACTIONS
ISOTHERMAL TGA (160°C)

<u>Sample</u>	<u>% UFAP</u>	<u>% PFM</u>	<u>% Wt. Loss</u>		<u>Time to 1% wt loss</u>
			<u>6 hours</u>	<u>20 hours</u>	
1	10	0.2	0.33	1.22	16.25
2	10	1.0	0.69	2.30	8.10
3	10	3.0	0.91	2.77	6.5
4	30	0.2	0.28	0.96	21.0
5	30	1.0	0.60	2.05	9.5
6	30	3.0	1.22	3.12	5.0
7	60	0.2	0.18	0.93	> 21.0
8	60	1.0	0.62	1.62	10.0
9	60	3.0	1.32	5.04	4.5

CONFIDENTIAL

Propellant Sample Size Effects

(U) A formulation of high burn rate thermally stable propellant was selected for manufacture as a master batch of propellant to be used in a series of small mixes to compare the relative stability of several burn rate catalysts and to determine if the sample size affects the previously drawn conclusions, since previous TGA data were obtained on small cubes of propellant. The master batch was to be subdivided into 600 gram lots. Into each of these 600 gram samples will be added 2% of several thermally stable burn rate catalysts.

(C) The formulation selected was one containing 70% AP and 16% Al powder. The polymer utilized was ARCO's R45M/HTPB polymer cured with IPDI. The oxidizer blend consisted of 25% freeze-dried AP (particle size 0.88 microns), 35% fluid-energy milled AP exhibiting a particle size of 2.1 micron and 40% 50 micron rounded AP. Each of the oxidizer samples were predried to minimum moisture contents and thermal stabilities determined on each of the fractions before mix manufacture. Thermal stabilities in excess of 30 hours at 375°F were obtained. The aluminum powder was predried at 110° under vacuum for 24 hours and the HTPB polymer was likewise vacuum dried and an antioxidant (A.O. 2246, 1%) was added to the polymer. The curing agent was dried over molecular sieves for 24 hours before utilization.

(U) The mix was manufactured in a one-gallon vertical mixer (9 lbs.) and mixed under vacuum. After all the ingredients were added (no curing agent nor catalyst was incorporated at this point), the mix was mixed at 170°F for 5 hours to eliminate moisture and other volatiles. The EOM viscosity was 18 Kp.

(U) Following completion of the mix, 600 gram samples were taken and sealed in aluminum foil. To each of the samples will be added 2% of several different thermally stable burning rate catalysts and two-inch cubes will be manufactured in order to determine the thermal stability character of each of these catalyzed formulations.

UNCLASSIFIED

Task II. Thermally Stable Catalysts

(U) Efforts to obtain thermally stable catalysts are proceeding essentially as planned. In Subtask 1, critical impurities were identified, and methods for removal were developed. In Subtask 2, molecular characteristics which contribute most to thermally stable catalysts were identified. The current report is concerned primarily with Subtask 3 which is the synthesis of improved catalysts based upon information gained in the two prior Subtasks.

(U) In the previous report, the stability data of propellants containing AP which had been aged at 25% relative humidity were reported. Fine, stable AP showed a marked improvement in a propellant catalyzed with benzoyl ferrocene. The large, stable AP showed a slight decrease in stability (Figures 1 and 2). It has been learned that the particle size of the fine, stable oxidizer approximately doubled during aging while that of the large, stable AP remained unchanged. This probably accounts for the change in stability of propellant containing fine, stable AP.

(U) Insoluble products which have no alpha hydrogen atoms present are being sought through the co-polymerization of ferrocene with acetone. It is hoped that polymerization conditions can be found which will yield an α, α -dimethylpolyferrocenylmethylene (DMPFM). Table I is a summary of reactions which have been attempted in order to prepare the desired products. A large number of variables has been investigated in this study. These include reaction time, temperature, order of addition or reaction sequence, catalyst and co-catalyst ratio, and acetone to ferrocene ratio.

(U) Two very attractive products have come from this work; the product from reaction 7 in Table II, and that from reaction 19. The elemental analysis of the reaction product number 7 (FeAc-7) is as follows: C64.79, 64.92; H6.17, 6.45; Fe22.57, 22.42. If it is assumed that the unaccounted composition is present as oxygen (halogens, sulfur, and nitrogen have been shown to be absent), then the empirical formula calculated is $C_{13}H_{16}FeO$. The product from reaction 19 (FeAc-19) gave the following analysis: C69.8; H6.5 (theoretical values for DMPFM are C69.09; H6.19; Fe24.71).

(U) Both of these products were totally insoluble in all solvents investigated (14 solvents). Purification of these compounds was accomplished by continuous Soxhlet extraction to remove all soluble components. Several solvents were used. The solubility properties and composition of the product are distinctly different from those reported by Paushkin.¹

1. Y. M. Paushkin, T. P. Vishnyakova, I. I. Patalakh, T. A. Sokolinskaya and F. F. Machus, Doklady Akad. Nauk. S. S. S. R., 149, No. 4, p. 856 (1963).

UNCLASSIFIED

TABLE II
REACTION CONDITIONS FOR DMPFM

No.	Fc(g)	$\text{CH}_3-\overset{\text{O}}{\underset{\text{ }}{\text{C}}}-\text{CH}_3(\text{g})$	Catalyst	Co-Catalyst	Product
1.	10	xs	5.3g H_2SO_4		Black insoluble solid
2.	10	4	xs H_3PO_4		Black insoluble solid
3.	10	4	Alc. KOH		Very little reaction
4.	10	xs	1 ml H_2SO_4	6.8 g ZnCl_2	Slight reaction
5.	10	6	5 ml H_2SO_4	0.1 g ZnCl_2	Orange solid
6.	10	6	5 ml H_2SO_4	0.1 g ZnCl_2	Orange solid
7.	10	6	5 ml H_2SO_4	0.1 g ZnCl_2	63% yield, orange solid
8.	10	6	5 ml H_2SO_4	0.1 g ZnCl_2	No reaction at 0°C
9.	10	6	5 ml H_2SO_4	0.1 g ZnCl_2	Charred black product at elevated temp.
10.	10	6	1 ml H_2SO_4	0.1 g ZnCl_2	Slight reaction
11.	100	60	50 ml H_2SO_4	1.0 g ZnCl_2	Reaction fumed off
12.	100	60	50 ml H_2SO_4	1.0 g ZnCl_2	32% yield, orange solid
13.	18.6	2.9	Na-Hg		No reaction
14.	18.6	116	HCl	4.8 g ZnCl_2	Low yield, soluble polymer
15.	18.6	116 (dry)	HCl	4.8 g dry ZnCl_2	11.2 g hexane soluble polymer
16.	18.6	11.6	HCl	4.8 g ZnCl_2	Ether solvent, low yield of product
17.	93	58	HCl	24.55 g ZnCl_2	Ether solvent. Carbonized product.
18.	18.6	11.6	HCl	13.6 g ZnCl_2	Ether, low yield
19.	18.6	17.4	HCl	13.6 g ZnCl_2	50% yield, yellow insoluble solid
20.	9.3	5.8	HCl	6.8 g ZnCl_2	Ether pre-saturated with HCl no reaction
21.	9.3	5.8	HCl	6.8 g ZnCl_2	Ether 50% saturated with HCl no reaction
22.	9.3	20	HCl	6.8 g ZnCl_2	10% soluble polymer some insoluble polymer
23.	9.3	20	HCl	6.8 g ZnCl_2	1% soluble polymer, no insoluble polymer
24.	18.6	11.6	HCl	9.5 g ZnCl_2	No reaction at 25°C

UNCLASSIFIED

(U) Small propellant mixes were made using these materials and the propellants were investigated in the standard TGA weight loss test as shown in Figure 1. Both materials appeared to be improvements over PFM, and are quite attractive. Note that at 8 hours, propellants made from the two new polymers had lost only 60% as much weight as those from PFM, which was the best catalyst of all the models studied.




Figure 1. TGA of Propellant at 320°F

CONFIDENTIAL

(U) Two components from Frankfort Arsenal have been made into propellant and evaluated in this same test. These include triferrocenylphosphineiron tetracarbonyl, and bis-(triferrocenylphosphine) iron tricarbonyl. These compounds were relatively quite good with regard to thermal stability, being among the better compounds tested, but not quite as good as the most stable model (PFM, see Figure 1.).

(U) A polymeric product similar to PFM in which one of the benzylic type hydrogen atoms had been replaced by a methyl group was prepared from hydroxyethylferrocene. The polymer was formulated into propellant and evaluated by a TGA test. It was not quite as attractive as PFM.

(U) Attempts have been made to obtain similar polymers, but these have not given the encouraging results seen with the acetone-ferrocene products.

(U) The polymerization of 2-ferrocenyl-2-butanol was attempted using the same conditions as those used for polymerizing hydroxymethylferrocene. However, no polymeric products were obtained.

(U) 2-Ferrocenylisopropanol was prepared from acetylferrocene and methyl-magnesium bromide. This was used in polymerization reactions to obtain a polyferrocenyl-methylene type polymer which contains no alpha hydrogens, however, better results were obtained in going directly from ferrocene and acetone.

(U) The polyrecombination of ferrocene to make polyferrocenylene was abandoned because of experimental difficulties. At the reaction temperature of 200°C ferrocene sublimed rapidly and flask outlets stopped up. Fires occurred during the reaction.

(U) The two insoluble ferrocene polymers; FcAc-7, the polymer obtained from ferrocene, acetone, zinc chloride, and sulfuric acid, and FcAc-19, the polymer using hydrogen chloride in place of sulfuric acid were made in 50-grain batches.

(U) Thermogravimetric analyses in nitrogen indicated that both polymers are stable up to approximately 750°F. In air the limit is 340°F for FcAc-7 and 355°F for FcAc-19. Differential scanning calorimetry indicated similar results.

(C) A cross-check of propellant burning rate efficiency was made on the two new catalysts. Propellant containing 89.5% solids was prepared using a formulation which is essentially the same as that of a propellant containing 2.5% n-butyl ferrocene and which has been evaluated in large motors and laboratory tests for several years. The formulation included 71% oxidizer (69% unground and 31% high speed grind, 16 micron) 16% aluminum, 2.5%

CONFIDENTIAL

(C)
catalyst, and 10.5% HC binder with a mixed curing system using a 5/1 ratio of MAPO to ERLA-0510, with 0.1% iron linoleate as a cure catalyst. The propellant was cured using a 1/0.84 ratio of carboxylic acid to curing agent. Mix 13Q-633 was made using butylferrocene as a standard; the end-of-mix viscosity was 14 Kp at 137°F. Mix 2198 used FcAc-19 as the catalyst at 2.5%, and had an end-of-mix viscosity of 140 Kp at 120°F. Mix 2199 used FcAc-7 as a catalyst and the end-of-mix viscosity was off-scale. The burning rate curves are shown in Figure 2. The new burning catalysts are about 90% as effective as P-IV even though they are insoluble solids.

◇ 13Q633, P-IV

○ 2198, FcAc-19

□ 2199, FcAc-7




Figure 2. Burning Rate Comparisons (U)

UNCLASSIFIED

(U) Sensitivity comparisons were made by performing impact, friction, and spark sensitivity determinations as well as differential thermal analyses upon propellants from the mixes mentioned above. This data is shown in Table III. The sensitivity of propellants made using the two new catalysts is comparable with the sensitivity of propellants made with butyl ferrocene. With regard to the differential thermal analysis, slightly higher temperatures are achieved before the initial exotherm occurs.

TABLE III

SENSITIVITY DATA (U)

<u>Catalyst (mix no.)</u>	<u>Spark (joules)</u>	<u>Friction (lbs)</u>	<u>Impact (Eo, Kg-cm)</u>	<u>DTA (initial exo.)</u>
FcAc-19 (2198)	-25	-85	-40 +50	386°F
FcAc-7 (2199)	-25	-75 +85	-50 +60	377°F
P-IV (13Q633)	-25	-75 +85	-40 +50	341°F

CONCLUSIONS:

(U) Two new catalysts, FcAc-7 and FcAc-19 have shown promise of good thermal stability in propellants by several criteria including DSC in air and in nitrogen, and TGA tests on neat catalyst and propellant. Burning rates have been evaluated in strands. The FcAc-19 product appears to be cleaner and more uniform, and to consist entirely of carbon, hydrogen and iron. The structure of FcAc-7 is less certain. Primarily for this reason, as well as the slight advantage in burning rate, it has been recommended that FcAc-19 be scaled-up for further evaluation under Task III. This recommendation has been accepted and scale-up will be instituted during the next reporting period.

UNCLASSIFIED

Page 1

CPIA DISTRIBUTION LIST

SECTION I

Copy 1
Central Intelligence Agency
Attn: CRS/ADD
Washington, D. C. 20505

Copy 2
Defense Res. & Engrg.
Attn: Propulsion Technology
Pentagon, 3D1065
Washington, D. C. 20301

Copy 3
NASA
Lewis Research Center
Attn: Librarian
21000 Brookpark Road
Cleveland, Ohio 44135

Copy 4
NASA
Kennedy Space Center
Attn: Library-ATS-132C
Kennedy Space Center, Fla. 32899

Copy 5
NASA
Manned Spacecraft Center
Attn: Library/Code BM6
Houston, Texas 77058

Copies 6,7,8
NASA
Langley Research Center
Attn: Librarian
Langley Station
Hampton, Va. 23565

Copies 9,10
NASA Scientific & Tech.
Info. Facility
Attn: SAF/DL, ACQ Div.
P. O. Box 33
College Park, Md. 20740

Copy 11
NASA
Attn: Code RPS
Washington, D. C. 20546

Copies 12,13
Defense Documentation Center
Attn: TSR
Cameron Station, Bldg. 5
Alexandria, Virginia 22314

Copy 14
AF Systems Command
Director of Laboratories
Attn: DLTP
Andrews AFB
Washington, D. C. 20331

Copy 15
AF Systems Command
Attn: DPSL, Library
Andrews AFB
Washington, D. C. 20331

Copy 16
AF Rocket Propulsion Lab.
Attn: RT
Edwards, Calif. 93523

UNCLASSIFIED

UNCLASSIFIED

CPIA Section I

Page 2

Copy 17

AF Rocket Propulsion Lab.
Attn: Technical Library
Edwards, Calif. 93523

Copy 18

AF Rocket Propulsion Lab.
Attn: RFR
Edwards, Calif. 93523

Copy 19

AF Rocket Propulsion Lab.
Attn: RPM
Edwards, Calif. 93523

Copy 20

AF Office of Scientific Research
Attn: SREP
1400 Wilson Blvd.
Arlington, Va. 22209

Copy 21

Army Ballistic Res. Labs
Attn: AMXBR-1
Aberdeen Proving Ground, Md. 21005

Copy 22

Frankford Arsenal
Attn: C2500-Library-B51-2
(for Propellant & Expl. Section)
Philadelphia, Pa. 19137

Copies 23, 24

Picatinny Arsenal
Scientific & Tech. Info. Br.
Attn: SMUPA-VA6, Librarian
Dover, New Jersey 07801

Copies 25 - 28

Army Missile Command
Redstone Scientific Info. Center
Attn: Chief, Document Section
Redstone Arsenal, Alabama 35809

Copy 29

White Sands Missile Range
Attn: Technical Library
White Sands MR, New Mexico 88002

Copy 30

Naval Air Systems Command
Attn: AIR-6042, Tech. Library
Washington, D. C. 20360

Copies 31

Naval Air Systems Cmd.
Attn: AIR-53664
Washington, D. C. 20360

Copy 32

Naval Ordnance Systems Cmd.
Attn: ORD-55211B
Washington, D. C. 20360

Copy 33

Naval Ordnance Systems Cmd.
Attn: ORD-0331
Washington, D. C. 20360

Copies 34, 35

Naval Ordnance Laboratory
Attn: Library
White Oak
Silver Spring, Maryland 20910

UNCLASSIFIED

UNCLASSIFIED

CPIA Section I

Page 3

Copies 36, 37
Naval Air Systems Cmd.
Attn: AIR-330
Washington, D. C. 20360

Copies 38 - 41
Naval Weapons Center
Attn: Code 753-Technical Library
China Lake, California 93555

Copy 42
Naval Postgraduate School
Attn: Librarian, Tech. Repts.
Section 2124
Monterey, California 93940

Copies 43, 44
Naval Ordnance Station
Attn: Technical Library
Indian Head, Maryland 20640

Copy 45
Naval Research Branch Office
Attn: Librarian
1030 East Green Street
Pasadena, California 91101

Copy 46
Naval Ordnance Systems Cmd.
Attn: ORD-9132
Tech. Library
Washington, D. C. 20360

Copy 47
Naval Research Lab.
Attn: Code 5117
Washington, D. C. 20390

Copy 48
Navy Strategic Systems Project Office
Attn: Technical Library
Munitions Bldg. Room 3245
Washington, D. C. 20360

Copy 49
Naval Underwater Weapons
Res. -Eng. Sta.
Attn: Tech. Library (CS12)
Newport, R.I. 02840

Copy 50
Naval Weapons Laboratory
Attn: Technical Library
Dahlgren, Virginia 22488

Copy 51
Naval Air Dev. Center
Attn: Librarian
Warminster, Pa. 18974

Copies 52, 53
Aerojet-General Corp.
Attn: Tech. Info. Ctr.
P. O. Box 13222
Sacramento, Calif. 95813

Copy 54
Philco-Ford Corp.
Aeronutronic Division
Attn: Tech. Info. Svcs. Acquisitions
Ford Road
Newport Beach, Calif. 92663

Copies 55, 56
Aerospace Corp.
Attn: Tech. Info. Ctr. -Doc. Group
P. O. Box 95085
Los Angeles, Calif. 90045

UNCLASSIFIED

UNCLASSIFIED

CPIA Section I

Page 4

Copies 57, 58
Susquehanna Corp.
Atlantic Research Group
Attn: Library
Shirley Highway at Edsall Rd.
Alexandria, Va. 22314

Copy 59
Bell Aerosystems Co.
Attn: Technical Library
P. O. Box 1
Buffalo, New York 14240

Copy 60
Boeing Co.
Attn: Aerospace Library-8K-38
P. O. Box 3999
Seattle, Washington 98124

Copies 61, 62
Chemical Propulsion Info. Agency
Applied Physics Lab-JHU
8621 Georgia Avenue
Silver Spring, Md. 20910

Copy 63
Lockheed Missiles & Space Co.
Attn: Tech. Info. Ctr., 50-14
3251 Hanover Street
Palo Alto, Calif. 94304

Copy 64
Dow Chemical Co.
Product Dept. Labs.
Attn: R. S. Karpluk, Bldg. 1710
Larkin Lab., 2020 Dow Center
Midland, Michigan 48641

Copy 65
Esso Research & Engineering Co.
Gov't. Res. Lab.
Attn: Defense Security Officer
P. O. Box 8
Linden, N. J. 07036

Copy 66
Hercules, Inc.
Allegany Ballistics Lab.
Attn: Technical Library
P. O. Box 210
Cumberland, Md. 21502

Copy 67
Hercules, Inc.
Research Center
Attn: Tech. Info. Center
Wilmington, Delaware 19899

Copy 68
Institute for Defense Analyses
Attn: Classified Library
400 Army-Navy Drive
Arlington, Virginia 22202

Copy 69
California Inst. of Technology
Jet Propulsion Laboratory
Attn: Library, TDS
4800 Oak Grove Drive
Pasadena, California 91103

Copies 70, 71
Lockheed Propulsion Co.
Attn: Library
P. O. Box 111
Redlands, California 92373

Copy 72
Aerospace Corporation
Marquardt Division; Library
P.O. Box 2013, So. Annex
Van Nuys, California 91409

Copy 73
Martin-Marietta Corp.
Attn: MP-30, Engineering Library
P. O. Box 5837
Orlando, Florida 32805

UNCLASSIFIED

UNCLASSIFIED

CPIA Section I

Page 5

Copy 74

North American Rockwell
Space & Information Systems Div.
Attn: Tech. Info. Ctr. -096-722
12214 Lakewood Blvd.
Downey, Calif. 90241

Copy 75

Rocket Research Corp.
Attn: Technical Library
Willow Road at 116th Street
Redmond, Washington 98052

Copies 76

North American Rockwell
Rocketdyne Division
Attn: Library Dept. 086-306
6633 Canoga Avenue
Canoga Park, Calif. 91304

Copies 77, 78

TRW Systems, Inc.
Attn: Technical Info. Center
One Space Park
Redondo Beach, Calif. 90278

Copy 79

Thiokol Chemical Corp.
Elkton Division
Attn: Tech. Info. Center
Elkton, Md. 21921

Copies 80, 81

Thiokol Chemical Corp.
Wasatch Division
Attn: Technical Library
Brigham City, Utah 84302

Copy 82

United Aircraft Corp.
Acquisitions Librarian
400 Main Street
West Hartford, Conn. 06108

Copy 83

United Aircraft Corp.
Pratt & Whitney Aircraft Div.
Attn: Head Librarian
P. O. Box 2691
West Palm Beach, Florida 33402

Copy 84

United Aircraft Corp.
United Technology Center
Attn: Technical Library
P. O. Box 358
Sunnyvale, Calif. 94088

Copy 85

Princeton University
Forrestal Campus Library
Attn: Librarian
P. O. Box 710
Princeton, N. J. 08540

Copy 86

Stanford Research Inst.
Attn: Document Center
For: M. E. Hill
333 Ravenswood Ave.
Menlo Park, Calif. 94025

Copy 87

LTV Aerospace Corporation
Missiles and Space Division
Attn: Librarian - 3-51000
P.O. Box 6267
Dallas, Texas 75222

UNCLASSIFIED

UNCLASSIFIED

15 December 1970

Page 1

CPIA DISTRIBUTION LIST

SECTION II

SECTION II Category 2 - Solid Propellant and Rocket Motor Programs

Copy 88
Army Ammo. Procurement
& Supply Agency
Attn: RDL, Quality Assurance
Tech. Library
Joliet, Illinois 60431

Copy 89
Foreign Technology Division
Attn: PDBP
Wright-Patterson AFB, Ohio 45433

Copy 90
McDonnell Douglas Corp.
Attn: Library
P. O. Box 516
St. Louis, Missouri 63166

Copy 91
Hercules, Inc.
Bacchus Works
Attn: Library 100-H-2
P. O. Box 98
Magna, Utah 84044

Copy 92
Hq., USAF
Attn: AFRDPS, A Eaffy
Washington, D.C. 20330

Copy 93
Northrop Carolina, Inc.
Attn: Library
P. O. Box 3049
Asheville, N. C. 28802

Copy 94
Olin Mathieson Chemical Corp.
Attn: Asst. Librarian
Mail Control Room
275 Winchester Avenue
New Haven, Connecticut 06504

Copy 95
Purdue University
School of Mechanical Engineering
Attn: B. A. Reese
Lafayette, Indiana 47907

Copy 96
North American Rockwell
Rocketdyne Division
Attn: Library
McGregor, Texas 76657

Copy 97
Shell Oil Co.
Shell Development Div.
P. O. Box 24225
Oakland, Calif. 94623

Copy 98
Aerospace Corp.
Attn: Library
P. O. Box 1308
San Bernardino, Calif. 92402

UNCLASSIFIED

Page 2

CPIA Distribution List

Section II Category 2 - Solid Propellant and Rocket Motor Programs

1 Copy 99
Los Alamos Scientific Laboratory
Attn: Report Library
P. O. Box 1663
Los Alamos, New Mexico 87544

1 Copy 100
Olin Mathieson Chemical Corp.
Attn: Research Library
P. O. Drawer G
Marion, Illinois 62959

UNCLASSIFIED
Security Classification

DOCUMENT CONTROL DATA - R&D		
(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)		
1 ORIGINATING ACTIVITY (Corporate author) Thiokol Chemical Corporation Huntsville Division Huntsville, Alabama		2a REPORT SECURITY CLASSIFICATION CONFIDENTIAL
		2b GROUP iv
3 REPORT TITLE Quarterly Progress Report, Thermally Stable Burning Rate Accelerators 1 June through 31 August 1971		
4 DESCRIPTIVE NOTES (Type of report and inclusive dates) Quarterly Progress Report, 1 June through 31 August 1971		
5 AUTHOR(S) (Last name, first name, initial) Flanigan, D.A. Stephens, W.D.		
6 REPORT DATE October	7a. TOTAL NO. OF PAGES 20	7b NO OF REFS 1
8a CONTRACT OR GRANT NO F04611-70-C-0066	9a. ORIGINATOR'S REPORT NUMBER(S) 32-71 Control No. C-71-32A	
b PROJECT NO 3148		
c		
d	9b OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
10 AVAILABILITY/LIMITATION NOTICES In addition to security requirements which must be met, this document is subject to special export controls and each transmittal to foreign governments or foreign nationals without prior approval of AFRPL(RPPR/STINFO)		
11 SUPPLEMENTARY NOTES	12 SPONSORING MILITARY ACTIVITY Air Force Systems Command Edwards Air Force Base, Cal.	
13 ABSTRACT Experiments have shown that the thermal stability of propellants is a direct function of UFAP and catalyst concentration. A new thermally stable catalyst has been synthesized and is undergoing preliminary evaluation. Indications are that fast burning propellants (2.5 in/sec at 1000 psi) can be made using up to 30% UFAP and up to 3% catalyst.		

DD FORM 1473
1 JAN 64

UNCLASSIFIED
Security Classification

UNCLASSIFIED
Security Classification

14 KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Burning rate accelerators UFAP Catalyst Thermal stability						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.

UNCLASSIFIED
Security Classification